

Super Stock Gas (6,500lbs)

1. Must have OEM drive train in factory location.
2. No sheet metal intakes allowed.
3. No aluminum heads.
4. single 4150 base carburetor, naturally aspirated.
5. Draw Bar or Reese (style) hitch must be no less than 42" from center line of axle to chain hook point. No part of the hitch may go passed center line of the rear axle.
6. Open headers allowed, as long as they are down and back.
7. Hitch height is 26". Must be rigid in all directions. No supports from hitch to rear axle.
8. No tires can measure larger than 33"x12.50". No cutting of the tires. Tires MUST be DOT approved.
9. Hanging weights are allowed. Weight bar can not exceed 6" from front bumper in stock location. Weights hanging directly below front bumpers are accepted.
10. Must have OEM or factory floor in bed. No cutting or gutting will be allowed.
11. Must have interior factory bench, and/or bucket seats. Must have factory dash pad.
12. Fuel cells allowed only in the bed of the truck.
13. Battery must be in factory location.
14. No alcohol or nitrous.
15. Must have at least 3 rear leaf springs.
16. If wheelbase exceeds 133", the truck must lose 2" of hitch height or 200lbs.
17. Factory power steering is required.
18. Electric water pumps are allowed.
19. must have working brakes on all four wheel.
20. Removable front and rear traction devices are allowed as long as they are removable.

Safety Regulations

1. If any of these regulations do not pass, you will automatically be disqualified.
2. S.F.I. approved bell-housing or transmission blankets. **HIGHLY RECOMMENDED.**
3. Operating kill switch near the hook point. **HIGHLY RECOMMENDED.**
4. S.F.I. approved steel flywheel and harmonic balancer. **HIGHLY RECOMMENDED.**
5. Must have drive shaft loops and u-joint shields on the rear u-joints.
6. Must have firewall.
7. Must have accessible fire extinguisher for driver.
8. DOT helmets are required for all drivers.
9. Tech committee has all final say.
10. Truck must be safe to pull.